



SUBMERSIBLE PUMP "OM-22"

THE SUBMERSIBLE PUMP "OM-22" IS DESIGNED FOR PUMPING CIVIL AND INDUSTRIAL WATER WITH THE PRESENCE OF ABRASIVE SUSPENDED SOLIDS. SOLID QUALITY CAST IRON CONSTRUCTION AND TUNGSTEN CARBIDE MECHANICAL SEAL MAKES THIS PUMP AN EXCELLENT SOLUTION FOR CIVIL ENGINEERING, MINING, AGGREGATE QUARRIES AND INDUSTRIAL WASTEWATER TREATMENT.

TECHNICAL SPECIFICATIONS

Pump body:	EN-GJL-200 cast iron
Mechanical seal:	tungsten carbide (WIDIA) in oil bath
Impeller:	cast iron single-channel
Filter:	Steel
Shaft:	stainless steel
Discharge:	Ø 75 mm
Power:	2,2 Kw – 4,5 A with direct starting - 400V - 2950 rpm / 50Hz 2,2 Kw – 4 A with direct starting - 480V - 3550 rpm / 60Hz
Power supply:	Three-phase 400V-50hz / 480-60hz
Protection class:	IP68
Insulation class:	F
Water temperature:	Up to 40°
PH:	6 ÷ 12
Max. immersion depth:	5 mt
Electric cable:	10 mt
Weight:	41 Kg
Dimensions A/B/W:	380/550/200

